



GALAXY UD-16RLC+ HIGH SPEED ECO SOLVENT PRINTER

Technical Specification

Model	Galaxy UD-16RLC+			
Printing Width	1600mm (5.25 ft)			
Printhead Config.	Epson - i3200-E1*1			
Drying	Fans + IR Heater			
Ink	Eco-Solvent			
RIP Software	Photoprint, Maintop			
Printing Speed (m ² /h)	1200 dpi	Draft	2 Pass	52 (m ² /h)
	1800 dpi	Standard	3 Pass	34 (m ² /h)
	2400 dpi	Quality	4 Pass	26 (m ² /h)
	3600 dpi	H. Quality	6 Pass	17 (m ² /h)
	4800 dpi	Backlit	8 Pass	13 (m ² /h)
Product	I3200-E1			
Lenght x Width x Height	69.1 x 59.4 x 35.6			
Weight (Kg)	82			
Number of Nozzles	3200			
Distance Between Nozzles (inch)	1/300 (same line)			
Number of Nozzle Rows	8			
Maximum Number of Ink Colors	4			
Resolution	300 npi/single line, 600 npi/double line			
Print Width (mm)	33.8			
Spray Freequency	43.2 (single point), 21.6 (multi point)			
Ink drop volume (pl)	3.8-6-12 (9.4)			